

Model 5100/5100HD Gas Analyzers for Measuring H₂S in Process Gas

Based on Tunable Diode Laser Absorption Spectroscopy (TDLAS)



Model 5100



Model 5100 HD

Model 5100 and 5100HD use sealed reference cells for continuous on-line analyzer verification and offers high specificity, sensitivity and extremely fast response speeds.

Features and Benefits

- || **Noncontact Measurement**
Noncontact measurement offers low maintenance
- || **All Digital Signal Processing**
32-bit microcontroller capable of sophisticated signal processing
- || **Web-Based Interface**
To interrogate the analyzer remotely, all you need is the IP address of the analyzer
- || **Connectivity**
Modbus, Ethernet, dry contacts and analog
- || **Real-Time Performance Monitoring**
Laser line-lock verification using internal reference cell
- || **NEMA 4 Enclosure houses the electronic components**
Designed for outdoor installation
- || **Fully-Integrated Sample Handling**
Standard feature
- || **Resistant to Contamination**
No interference from gas phase amines, glycol, methanol, and mercaptans
- || **Hazardous Area Certifications for Model 5100 (pending for Model 5100HD)**
NEC/CEC: Class I, Div 2, Groups A,B,C,D; Class II, Div 2, Groups F & G; Class III

Model 5100/5100HD Gas Analyzers

Specifications

Laser Specification: Class IIIb

Typical Operating Range:

0-5000 ppm Min / 0 to 30% Max; Other ranges available subject to application-consult AMETEK.

Limit of Detection: 500 ppm

Accuracy: 1% of reading or ± 500 ppm or whichever is higher

Repeatability: 1% of reading or ± 500 ppm or whichever is higher

Linearity: Better than 1%

Environment:

Ambient Temperature: -20°C to +50°C (-4°F to 122°F). Max. temp for 5100HD is 100°C

Electrical Classification for Model 5100 (All Pending for Model 5100HD):

NEC/CEC: Class I, Div 2, Groups A,B,C,D; Class II, Div 2, Groups F & G; Class III

Relative Humidity: 0% to 90%, non-condensing

Sample Flow Rate: 1 to 10 SLPM recommended (2 - 20 SCFH)

Sample Cell Pressure: 70 to 170 kPa absolute (10-25 psia)

Speed of Response: < 1 second photometric response. Total system response is dependent on sample flowrate.

Outputs: 4-line x 20-character alphanumeric VF display.

Fast Ethernet (IEEE802.3)

RS-485 serial port, isolated (supports Modicon Modbus RTU)

(1) isolated 4-20 mA loop-powered analog output

(4) dry relay contacts. Contact rating 30 VAC, 60 VDC, 100 VA resistive

Electrical Requirements:

120 VAC (108-132V); 47-63 Hz, or 240 VAC (216-264V), 47-63 Hz

Power Requirements:

Model 5100: < 25W; with optional heater 105W
Model 5100HD: 450W with optional heater

Physical:

Model 5100 (HxWxD):
86.88 cm x 43.42 cm x 21.17 cm
(34.2" x 17.1" x 8.34")

Model 5100 HD (HxWxD):
64.23 cm x 83.03 cm x 29.53 cm
(25.29" x 32.69" x 11.63")

Weight:

Model 5100-25 Kg (55 lb)
Model 5100HD-58.97 Kg (130 lb)

Enclosure: IP-65, NEMA 4



150 Freeport Road, Pittsburgh, PA 15238
Ph. +1-412-828-9040, Fax +1-412-826-0399
www.ametekpi.com



© 2009, by AMETEK, Inc.
All rights reserved. Printed in the U.S.A.
F-0292 Rev. 1 (1009)

One of a family of innovative process analyzer solutions from AMETEK Process Instruments.
Specifications subject to change without notice.

SALES AND MANUFACTURING:

USA - Delaware
455 Corporate Blvd., Newark DE 19702 • Tel: +1-302-456-4400, Fax: +1-302-456-4444

USA - Oklahoma
2001 N. Indianwood Ave., Broken Arrow OK 74012 • Tel: +1-918-250-7200, Fax: +1-918-459-0165

CANADA - Alberta
2876 Sunridge Way N.E., Calgary, AB T1Y 7H9 • Tel: +1-403-235-8400, Fax: +1-403-248-3550

WORLDWIDE SALES AND SERVICE LOCATIONS:

USA - Texas
Tel: +1-713-466-4900, Fax: +1-713-849-1924

CHINA
Beijing / Tel: 86 10 8526 2111, Fax: 86 10 8526 2141
Chengdu / Tel: 86 28 8675 8111, Fax: 86 28 8675 8141
Guangzhou / Tel: 86 20 8363 4768, Fax: 86 20 8363 3701
Shanghai / Tel: 86 21 5868 5111, Fax: 86 21 5866 0969

FRANCE
Tel: 33 1 30 68 89 20, Fax: 33 1 30 68 89 29

GERMANY
Tel: 49 21 59 91 36 0, Fax: 49 21 59 91 3639

INDIA
Tel: 91 80 6782 3200, Fax: 91 80 6782 3232

MIDDLE EAST - Dubai
Tel: 971 4 881 2052, Fax: 971 4 881 2053

SINGAPORE
Tel: 65 6484 2388, Fax: 65 6481 6588