

## PRODUCT DATA SHEET

# 5800 Moisture Analyzer

## Excellent performance for critical moisture measurements

For critical moisture measurement applications, the 5800 offers a combination of exceptional performance benefits: high accuracy, multi-gas compatibility, fast response speed, and wide measurement range. The 5800 is ideal for moisture applications that require accurate results. The NIST-traceable internal moisture generator allows the user to quickly confirm analytical performance, at any time, on the sample gas. The generator adds a known amount of moisture to conditioned gas. The resulting known wet gas is then directed to the analyzer's sensor, verifying proper sensor and system operation. An alarm contact alerts the operator if the analyzer fails this verification process. The verification sequence may be started on a programmed schedule or on demand.

### Multi-gas compatibility

The 5800 is completely compatible with virtually all non-corrosive gases, including inerts – helium (He), argon (Ar), neon (Ne), xenon (Xe) and krypton (Kr) – oxygen (O<sub>2</sub>), hydrogen (H<sub>2</sub>), nitrogen (N<sub>2</sub>), nitric oxide (NO), carbon monoxide (CO), hydrocarbons, air, and many specialty gases such as sulfur hexafluoride (SF<sub>6</sub>). Changing gases is simple and quick.

### Fast response speed

The 5800 reaches 63% of a steady state reading in less than five minutes, far faster than other moisture analyzers in the 0.1 to 100 parts per million by volume (ppmv) range. Because the analyzer employs unique non-equilibrium measurement techniques, it delivers this exceptional response during dry-down as well as when wetting-up.

### Wide measurement range

The 5800 measures from 0.02 ppmv (20 parts per billion by volume (ppbv)) to 1000 ppmv. The calibrated range is 0.1 ppmv to 100 ppmv. Two custom-settable 4-20 mA outputs are provided, which may be assigned to cover any portion of the operating range. One analog output is auto-ranging, to maintain high output resolution over the widest measurement range possible.



## KEY BENEFITS

- Most accurate trace moisture measurement technology available
- Responds faster to both increasing and decreasing moisture levels
- Specific to moisture in most applications

## APPLICATIONS

- High-purity gas production
- Olefin production, storage, and transmission
- Semiconductor gases

## KEY MARKETS

- Semiconductor manufacturing
- Industrial gas
- Petrochemical

## PERFORMANCE SPECIFICATIONS

<b>Compatible gases</b>	Inerts (He, Ar, Ne, Xe, Kr), O <sub>2</sub> , H <sub>2</sub> , N <sub>2</sub> , NO, CO, hydrocarbons, air, and many specialty gases such as SF <sub>6</sub> . Carbon dioxide (CO <sub>2</sub> ) requires a custom measurement cell. (Contact the factory to confirm compatibility with other gases)
<b>Range</b>	0.02 to 100 ppmv. Indicates trend to 1000 ppmv. Display is software-settable to show ppmv, ppbv, or dew point temperature (requires pressure input)
<b>Limit of detection</b>	0.02 ppmv
<b>Accuracy</b>	±20 ppbv or 5% of the reading, whichever is greater
<b>Sensitivity</b>	5 ppbv or 0.5% of instrument range, whichever is greater
<b>Response time</b>	63% of a step change in either direction in less than five minutes
<b>Inlet pressure</b>	1 to 6.89 Bar (15 to 100 psig)
<b>Exhaust pressure</b>	Atmospheric
<b>Sample flow requirements</b>	600 ml/min at STP
<b>Sample gas temperature</b>	0 to 100°C (32 to 212°F)
<b>Outputs</b>	Four-line x 20-character vacuum fluorescent digital display. Two fully programmable 4-20 mA analog outputs, into 1200-ohm load RS485 bidirectional serial port
<b>Alarms</b>	Three independent contact closures, 32 V dc maximum, 1 A noninductive load, for system alarm, range alert/or calibration alert, concentration alert/or calibration alert. Alarm signals are available on the RS485 interface
<b>Software features</b>	Displays ppmv or ppbv moisture reading or dew point temperature, timer status, and instrument status
<b>Environmental</b>	4 to 40°C (40 to 105°F), 90% relative humidity, non-condensing, noncorrosive atmosphere. Optimal performance in ppbv applications is achieved when the ambient temperature is maintained within ±2°C
<b>Utility requirements</b>	85 to 265 volts, 47 to 63 Hz
<b>Mounting options</b>	Available for stand-alone or 19-inch rack installation
<b>Dimensions (W x H x D)</b>	432 x 132 x 381 mm (17 x 5.2 x 15 in.)
<b>Rack-mount version</b>	Same as above except height is 221 mm (8.71 in.)
<b>Net weight</b>	16.79 kg (37 lbs.)
<b>Approvals and certifications</b>	NEC Class I, Division 2, Groups A, B, C, D EU EN50081/82; EN61010-1

## SALES, SERVICE &amp; MANUFACTURING

**USA - Pennsylvania**

150 Freeport Road  
Pittsburgh PA 15238  
Tel: +1 412 828 9040  
Fax: +1 412 826 0399

**USA - Delaware**

455 Corporate Blvd.  
Newark DE 19702  
Tel: +1 302 456 4400  
Fax: +1 302 456 4444

**Canada - Alberta**

2876 Sunridge Way NE  
Calgary AB T1Y 7H9  
Tel: +1 403 235 8400  
Fax: +1 403 248 3550

## WORLDWIDE SALES AND SERVICE LOCATIONS

**USA**

Tel: +1 713 466 4900  
Fax: +1 713 849 1924

**Brazil**

Tel: +55 19 2107 4100

**France**

Tel: +33 1 30 68 89 20  
Fax: +33 1 30 68 89 99

**Germany**

Tel: +49 2159 9136 0  
Fax: +49 2159 9136 39

**India**

Tel: +91 80 6782 3200  
Fax: +91 80 6780 3232

**Singapore**

Tel: +65 6484 2388  
Fax: +65 6481 6588

**China**

Beijing  
Tel: +86 10 8526 2111  
Fax: +86 10 8526 2141  
Chengdu  
Tel: +86 28 8675 8111  
Fax: +86 28 8675 8141  
Shanghai  
Tel: +86 21 5868 5111  
Fax: +86 21 5866 0969



© 2018, by AMETEK, Inc. All rights reserved. Printed in the U.S.A. F-0130 Rev 5 (1018)  
One of a family of innovative process analyzer solutions from AMETEK Process Instruments. Specifications subject to change without notice.

