

## PRODUCT DATA SHEET

# 5100P TDLAS Moisture Analyzer

Lightweight and rugged portable moisture (water vapor) analyzer delivering reliable, accurate measurements in natural gas

The 5100P analyzer provides simple, easy-to-use moisture analysis using tunable diode laser absorption spectroscopy (TDLAS) in a durable, lightweight, and portable package for measurements in natural gas. Designed to be intuitive to start-up and log data, the 5100P is the tool-of-choice for users needing to perform measurements in remote locations or verify fixed analyzer installations.

### Minimal maintenance required

The non-contact TDLAS sensing technology means that both the laser source and the detector are kept separate from the process. This eliminates the need for routine calibration, cleaning of the sensor or interferences from process contaminants, increasing measurement uptime and reducing total cost of ownership.

To reduce the possibility of over pressuring the cell, or introducing contaminants, an integrated sample conditioning panel is included with the 5100P analyzer.

### Measurement confidence

To ensure accurate measurement, every 5100P is factory calibrated and tested prior to shipment. The 5100P also uses an internal reference to prevent any wavelength shift, when operated in the field. Although the 5100P, with its high-sensitivity, moisture-specific measurement will not be impacted by other constituents in the natural gas, the laser-source output must be monitored and controlled continuously to deliver an accurate moisture measurement every time.

### Increased efficiency

With an integrated sample system, using the 5100P is simple and easy. A measurement can be made in minutes, just connect the sample tubing, power up the analyzer, and start flow through the system. The TDLAS technology in the 5100P delivers immediate response to changes in the moisture content of the natural gas. Users no longer have to wait hours for the sensor to equilibrate and can make more measurements in less time. The 5100P is certified for use in hazardous areas so there are no costly enclosures or hot work permits needed to operate the analyzer.



## KEY BENEFITS

- Fast response, highly accurate measurements using TDLAS technology
- Certified for use in hazardous areas
- Integrated sample system removes contaminants
- Rechargeable battery for at least eight hours of operation
- Lightweight package simplifies transporting the device between locations

## APPLICATIONS

- Monitoring H<sub>2</sub>O in natural gas pipelines, processing and fuel lines

## KEY MARKETS

### NATURAL GAS

- Transmission pipelines
- Custody transfer
- Dehydration
- Underground storage
- Gas processing
- Gas compressor and metering stations

## PERFORMANCE SPECIFICATIONS

<b>Technology</b>	Tunable diode laser absorption spectroscopy
<b>Speed of response</b>	<1 second photometer response; <15 seconds to T90 at 2 SLPM of sample gas
<b>Range</b>	0 – 2500 ppmv
<b>Accuracy</b>	2% of reading or +/- 4 ppmv (whichever is greater)
<b>Repeatability</b>	2% of reading or +/- 4 ppmv (whichever is greater)
<b>Limit of detection</b>	5 ppmv in methane
<b>User interface</b>	On board display and USB
<b>Battery type</b>	Rechargeable sealed lead acid battery
<b>Sample cell pressure</b>	Atmospheric
<b>Ambient temperature</b>	-20 to +50°C (-4 to +122°F)
<b>Sample temperature</b>	-20 to +50°C (-4 to +122°F)
<b>Inlet pressure range for sample panel</b>	1.03 to 17.2 barg (15 to 250 psig)
<b>Recommended sample flow rate</b>	1 to 2 SLPM (2 to 4 SCFH)
<b>Physical dimensions</b>	25.1 cm x 20.9 cm x 40.1 cm (9.9 in x 8.2 in x 15.8 in); approximately 13.2 kg (29.1 lbs)
<b>Sample wetted parts</b>	304 Stainless steel, 316 stainless steel, SiO2 glass, EPDM
<b>Power requirements</b>	110-240 VAC 50-60 Hz for battery charging and instrument use when battery is depleted
<b>Environmental rating</b>	Pollution degree: 2 Overvoltage category: I Maximum altitude: 2000 meters Ingress rating: IP 65
<b>Pending certifications</b>	ATEX/IEC Ex II 3G na IC Op is IIC T3 Gc -20°C < Tamb < +50°C NEC Class 1, Div 2, GRP A, B, C, D, T3 -20°C to +50°C

### SALES, SERVICE & MANUFACTURING

#### USA - Pennsylvania

150 Freeport Road  
Pittsburgh PA 15238  
Tel: +1 412 828 9040  
Fax: +1 412 826 0399

#### USA - Delaware

455 Corporate Blvd.  
Newark DE 19702  
Tel: +1 302 456 4400  
Fax: +1 302 456 4444

#### Canada - Alberta

2876 Sunridge Way NE  
Calgary AB T1Y 7H9  
Tel: +1 403 235 8400  
Fax: +1 403 248 3550

### WORLDWIDE SALES AND SERVICE LOCATIONS

#### USA - Houston, Texas

Tel: +1 713 466 4900  
Fax: +1 713 849 1924

#### Brazil

Tel: +55 19 2107 4100

#### France

Tel: +33 1 30 68 89 20  
Fax: +33 1 30 68 89 99

#### Germany

Tel: +49 2159 9136 0  
Fax: +49 2159 9136 39

#### India

Tel: +91 80 6782 3200  
Fax: +91 80 6780 3232

#### Singapore

Tel: +65 6484 2388  
Fax: +65 6481 6588

#### China

Beijing  
Tel: +86 10 8526 2111  
Fax: +86 10 8526 2141  
Chengdu  
Tel: +86 28 8675 8111  
Fax: +86 28-8675 8141  
Shanghai  
Tel: +86 21 5868 5111  
Fax: +86 21 5866 0969



© 2018, by AMETEK, Inc. All rights reserved. Printed in the U.S.A. F-0544 (0718)  
One of a family of innovative process analyzer solutions from AMETEK Process Instruments. Specifications subject to change without notice.



To find out more or request a quote visit our website

[ametekpi.com](http://ametekpi.com)